MX

ECOBULK Feeder

SCHÜTZ INDUSTRIAL PACKAGING
The Future's Technology. Today.

www.schuetz.net

Lower costs by simplifying handling during production.

Shuttle IBC

Base IBC

- Reduction of idle times when changing containers.
- Gravimetrical emptying of transport containers keeps product loss at a minimum.
- Production process is not interrupted.
- Packaging materials are avoided.
- Replaces small packaging units.
- Time-effective draining of residuals.

Please do not hesitate to contact us regarding any technical concerns or questions.

DESIGN

Steel frame
- supports of special sheet metal, galvanized

Base IBC
- MX 1250

Shuttle IBC
- exchangeable
- MX 820 or MX 1000

PALLETS (4-way entry)

CERTIFICATIONS

- **UN 31 HA1/Y** (optional)

CAPACITY

MX 1250
1,250 litres (330 gal)

FILLING OPENING (base IBC)

- DN 150 with screw cap

OUTLET VALVE (base IBC)

- integrated butterfly valve DN 50
- screwable butterfly valve DN 50
- screwable ball valve DN 50

DIMENSIONS

Length:	1,310 mm
Width:	1,110 mm
Frame height:	1,782 mm
Height with MX 1000 stacked:	2,865 mm

WEIGHT

MX 1250:	70.0 kg
Frame:	117.0 kg
Fitting:	2.0 kg
Total:	**approx. 190 kg**